ASSEMBLY INSTRUCTIONS PLACE 'n PICK™ SHELF CART

DESCRIPTION

29" I ÓNG

LOWER SIDE

MEMBER

The Place 'n Pick[™] Shelf Cart Kit System allows user to assemble a highly versatile mobile shelving unit, equip it with bin boxes (not included) if desired, then roll it where needed in the work area. Shelves may be adjusted for optimum height and angle. Maximum rated capacity is 100 lbs per shelf. Cart is available as complete kit, including three 12" deep x 30", 42", 54" or 66" wide shelves (Model numbers HWP-SC30 [42] [54] [66]), or as cart frame only to fit 30", 42", 54" or 66" wide shelves or other accessories such as Bin Bar. Shelves are not included with cart frame kits. Shelves and other accessories must be ordered separately. See listing, page four.

NOTE: Prior to assembly, become familiar with the following instructions and names of components as shown below. Figure 1. COMPONENTS SHELVES WITH TRAK CLAMP BARS Standard kit includes three 30"W x 12"D shelves. 30", 42", 54" or 66" wide shelves in either 12" or 18" depth must be added to frame kit with corresponding width. Refer to components list, page 4, or contact your T-PLATE local Hubbell Workplace Solutions distributor for more information END CAP IMPORTANT ASSEMBLY NOTES 30.38", 42.38", 1. Components are assembled 54.38", or 66.38" LONG CROSS using the Hubbell Workplace T-PLATE MEMBER Solutions "ALIGN - SET -TIGHTEN" system; i.e. brackets END are clamped to aluminum CAP extrusions with track nuts inside 48" LONG one of the two cavities. UPRIGHT Always install single bolt track nuts with widest dimension perpendicular to aluminum rail. T-PLATE 45° ANGLE BRACE 2. All main frame BRACKET members are extruded aluminum ANGLE rail. Install horizontal members BRACKET with large cavity down. END T-PLATE 3. Shelves and all brackets are CAP steel and shipped with assembly hardware (usually track nuts) CROSS MEMBER . installed. Some track nuts may SWIVEL CASTER have to be reversed (bolt head with WRENCH 45° ALUMINUM ANGLE BRACE on opposite side of plate) for proper assembly.


45° ANGLE

BRACE


BRACKET

ASSEMBLY

- 1. Lay out all components. Locate shelves, casters, and plastic end caps (Fig. 1) and set aside.
- Locate two angle brackets and two T-plates. Place two 29" aluminum frame members on floor with large slot down. Affix angle brackets and T-plates to side members by sliding track nuts into aluminum rails. Position as shown in Figure 2, and tighten track nuts to secure.




NOTE: Position short (single bolt) track nuts with long dimension running across opening in aluminum rail.



ASSEMBLING LOWER SIDE MEMBERS

 Locate two 48" long uprights and two T-plates. Affix T-plates to uprights as shown in Fig. 3. Wrench tighten to secure.

NOTE:



 Assemble one upright to corresponding lower side frame assembly by sliding onto angle bracket. Tighten. Repeat for other side (Fig. 4).





Figure 4. ASSEMBLING UPRIGHTS TO LOWER SIDE MEMBERS


 Assemble angle braces to frame lower side members and uprights by simultaneously sliding one 45° bracket and angle brace into lower side member and the other 45° bracket down into angle brace and upright. Securely tighten all bolts (Fig. 5).



6. Lay one side frame flat and slide two cross members into T-plates. Slide cross members tight against side frame members and securely tighten track nut bolts (Fig 6).


ALUMINUM CROSS MEMBERS.

 Loosen clamp bars on shelf and Bin Bar (if used) mounting brackets. Mount shelves and Bin Bar to frame by sliding down from top with clamp bars inside uprights (Fig 8). Refer to additional instructions in Shelf or Bin Bar Kits. Position as desired. Tighten securely.



9. Adjust shelves at desired angle(s). Refer to instructions in Shelf Kits for more information.

10. Install casters with wrench included (Fig 9).



- 11. Install end caps and cover strip (Fig 10).
- Check to make sure all bolts are tight and that unit is square (all four casters firmly on floor). Adjust as necessary.

COMPONENT LISTING	
DESCRIPTION	MODEL NO.
Complete Cart Kit-(3) 12"D x 30"W Shelves included Complete Cart Kit-(3) 12"D x 42"W Shelves included Complete Cart Kit-(3) 12"D x 54"W Shelves included Complete Cart Kit-(3) 12"D x 66"W Shelves included	HWP-SC42 HWP-SC54
Frame Kit-For 30" Wide Shelves (Shelves NOT included) Frame Kit-For 42" Wide Shelves (Shelves NOT included) Frame Kit-For 54" Wide Shelves (Shelves NOT included) Frame Kit-For 66" Wide Shelves (Shelves NOT included)	HWP-SC04 HWP-SC05
Shelf-12"D x 30"W Shelf-12"D x 42"W Shelf-12"D x 54"W Shelf-12"D x 66"W	WS50-SS04 WS50-SS05
Shelf-18"D x 30"W Shelf-18"D x 42"W Shelf-18"D x 54"W Shelf-18"D x 66"W	WS50-SS184 WS50-SS185
Bin Bar-36" (Fits 30"W Frame Kit) Bin Bar-48" (Fits 42"W Frame Kit) Bin Bar-60" (Fits 54"W Frame Kit) Bin Bar-72" (Fits 66"W Frame Kit)	WS50-BB04A WS50-BB05A
Cover Strip-20' long roll. Cut to length.	WA-CS20



Figure 10. COMPLETED UNIT

P.O. Box 26 • 600 South Clark St. Mayville, WI 53050 Phone 920–387–5195



Workplace Solutions